CNT

肯耐特电子



科技铸就精品 品质盛誉全球

CNT

肯耐特电子

CONNECTOR

专业连接器制造商



公司简介

Company Introduces

盐城市肯耐特电子有限公司是一家设计、研发、生产、销售各种精密电子连接器的专业制造厂商，公司以多年在华南地区服务各类仪器仪表、电脑主板及数码产品的高端客户的经验，为更好的服务江浙沪地区的客户，于07年6月设立华东工厂，11年4月成立昆山分公司，以生产各种精密电子连接器为基础，开发、生产各类小间距精密产品为市场导向，并坚持走专业化、自动化的发展方针；于2011年8月通过ISO9001:2008质量管理体系认证；2014年7月成功导入ERP系统，以其科学的管理和先进的质量检测手段，力求高效地为客户提供优质、优价的产品。

公司产品广泛应用于计算机主板，各种移动存储盘、读卡器、数码产品、工业仪器仪表、智能电表、手机、平板电脑、车载系统、LED显示器、电子玩具、医疗设备等诸多领域。

回首过去的努力，肯耐特电子将始终以满足客户需求，以专业的精神创新技术，在未来精准而有效率的达成目标，为合作伙伴谋求更多的回报和尊重。

质量方针

质量有效管理
产能不断提升
客户服务满意

经营理念


质量第一
信誉第一
客户至上

环境政策

遵守法令法规
预防环境污染
制造绿色产品




1、0.8mm双排针，SMT
Spec:0.8mm Pin Header,Dual Row,SMT
Positions:2-100PIN
Plastics Height:1.38mm
Materials:Nylon-6T UL94V-0
P/N:CNT-M080-2*XX-GM-A/B/W




2、0.8mm双排母座，SMT
Spec:0.8mm Female Header,Dual Row,SMT
Positions:10-100PIN
Plastics Height:3.1mm
Materials:Nylon-6T UL94V-0
P/N:CNT-F080-2*XX-GM-310




3、1.0mm双排排针，180度
Spec:1.0mm Pin Header,Dual Row,Straight
Positions:4-80PIN
Plastics Height:1.0mm
Materials:Nylon-6T UL94V-0
P/N:CNT-M100-2*XX-GS-A/B



4、1.0mm双排排针，90度
Spec:1.0mm Pin Header,Dual Row,Right angle
Positions:4-80PIN
Plastics Height:1.0mm
Materials:Nylon-6T UL94V-0
P/N:CNT-M100-2*XX-GD-A/E/B




5、1.0mm双排排针，SMT
Spec:1.0mm Pin Header,Dual Row,SMT
Positions: 4-80PIN
Plastics Height:1.0
Materials:Nylon-6T UL94V-0
P/N:CNT-M100-2*XX-GM-A/E/B




6、1.0mm双排母座，SMT
Spec:1.0mm Female Header,Dual Row,SMT
Positions:4-80PIN
Plastics Height: 2.0mm
Materials:Nylon-6T UL94V-0
P/N:CNT-F100-2*XX-GM-200/5.0



7、1.27mm双排排针，DIP180度
Spec:1.27mm Pin Header,Dual Row, Straight
Positions:2-80PIN
Plastics Height:1.0 / 1.5/2.0/2.5 mm
Materials:Nylon-6T UL94V-0
P/N:CNT-M127-2*XX-GS-A/B



8、1.27mm双排双层排针，DIP180度
Spec:1.27mm Pin Header,Dual Row,Board Spacer,Straight
Positions:2-80PIN
Plastics Height:1.0 / 1.5/2.0/2.5 mm
Materials:Nylon-6T UL94V-0
P/N:CNT-M127-2*XX-GS-A/E/B



9、1.27mm双排排针，DIP90度
Spec:1.27mm Pin Header,Dual Row, Right angle
Positions:2-80PIN
Plastics Height:1.0 / 1.5/2.0/2.5 mm
Materials:Nylon-6T UL94V-0
P/N:CNT-M127-2*XX-GD-A/B/E




10、1.27mm双排排针，SMT带导柱
Spec:1.27mm Pin Header,Dual Row, SMT With Peg
Positions:2-80PIN
Plastics Height:1.0 / 1.5/2.0/2.5 mm
Materials:Nylon-6T UL94V-0
P/N:CNT-M127-2*XX-GM-A/B/W




11、1.27mm双排双层排针，SMT带导柱
Spec:1.27mm Pin Header,Dual Row, Board Spacer,SMT With Peg
Positions:2-80PIN
Plastics Height:1.0 / 1.5/2.0/2.5 mm
Materials:Nylon-6T UL94V-0
P/N:CNT-M127-2*XX-GM-A/B/W/E-P



12、1.27mm单排母座，180度直插
Spec:1.27mm Female Header,Single Row,Straight
Positions:2-40PIN
Plastics Height:2.1/4.3mm
Materials:Nylon-6T UL94V-0
P/N:CNT-F127-1*XX-GS-H/B




13、1.27mm双排母座，180度直插
Spec:1.27mm Female Header,Dual Row,Straight
Positions:4-80PIN
Plastics Height:2.1/4.3mm
Materials:Nylon-6T UL94V-0
P/N:CNT-F127-2*XX-GS-H/B



14、1.27mm单排母座，SMT
Spec:1.27mm Female Header,Single Row,SMT
Positions:2-40PIN
Plastics Height:2.1/4.3mm
Materials:Nylon-6T UL94V-0
P/N:CNT-F127-1*XX-GM-H/W



15、1.27mm双排母座，SMT
Spec:1.27mm Female Header,Dual Row,SMT
Positions:4-80PIN
Plastics Height: 2.1/4.3mm
Materials:Nylon-6T UL94V-0
P/N:CNT-F127-2*XX-GM-H/W



16、1.27mm双排母座，SMT带导柱
Spec:1.27mm Female Header,Dual Row,SMT With Peg
Positions:4-80PIN
Plastics Height:4.3mm
Materials:Nylon-6T UL94V-0
P/N:CNT-F127-2*XX-GM-430/4.8-P




17、1.27mm双排母座，SMT外带导柱带凸
Spec:1.27mm Female Header,Dual Row,SMT With Peg
Positions:4-80PIN
Plastics Height:4.4mm
Materials:Nylon-6T UL94V-0
P/N:CNT-F127-2*XX-GM-440/4.8-P-T




18、1.27mm分体式简易牛角，180度
Spec:1.27mm Box Header Dual Row,Straight DIP
Positions:6-100PIN
Plastics Height:5.7/11.2/10.7/15.6…mm
Materials:NYLON 6T
P/N:CNT-B127-2*XX-GS-H/B



19、1.27mm加高简易牛角，SMT带导柱
Spec:1.27mm Box Header Dual Row,SMT With Peg
Positions:6-100PIN
Plastics Height:5.7/11.2/10.7/15.6…mm
Materials:LCP
P/N:CNT-B127-2*XX-GM-H/W-P




20、1.27*2.54mm公座，SMT
Spec:1.27*2.54mm PIN HEADER
Positions:4-80PIN
Plastics Height:2.54mm
Materials: NYLON 6T
P/N:CNT-M127*2.54-2*XX-GM




21、1.27*2.54mm母座，180度DIP
Spec:1.27*2.54mm Female HEADER,Straight DIP
Positions:4-80PIN
Plastics Height:8.5mm
Materials: Nylon-6T UL94V-0
P/N:CNT-F127*2.54-2*XX-GS-850




22、1.27*2.54mm简牛，180度DIP
Spec:1.27*2.54mm BOX HEADER,Straight DIP
Positions:4-80PIN
Plastics Height:
Materials: Nylon-6T UL94V-0
P/N:CNT-B127*2.54-2*XX-GS




23、2.0mm双排排针，DIP180度
Spec:2.0mm Pin Header,Dual Row,Straight
Positions:4-80PIN
Plastics Height:1.0 / 1.5/2.0mm
Materials:Nylon-6T UL94V-0
P/N:CNT-M200-2*XX-GS-A/B




24、2.0mm双排双层排针，DIP180度
Spec:2.0mm Pin Header,Dual Row,Board Spacer,Straight
Positions:4-80PIN
Plastics Height:1.0 / 1.5/2.0mm
Materials:Nylon-6T UL94V-0
P/N:CNT-M200-2*XX-GS-A/E/B




25、2.0mm单排排针，DIP90度
Spec:2.0mm Pin Header,Single Row,Right Angle
Positions:2-40PIN
Plastics Height:1.0 / 1.5/2.0mm
Materials:Nylon-6T UL94V-0
P/N:CNT-M200-1*XX-GD-A/B/E




26、2.0mm双排双层排针，DIP90度
Spec:2.0mm Pin Header,Dual Row,Board Spacer,Right Angle
Positions:4-80PIN
Plastics Height:1.0 / 1.5/2.0mm
Materials:Nylon-6T UL94V-0
P/N:CNT-M200-2*XX-GD-A/E/B/F




27、2.0mm单排双层排针，SMT
Spec:2.0mm Pin Header,Single Row,Board Spacer,SMT
Positions:2-40PIN
Plastics Height:1.0 / 1.5/2.0mm
Materials:Nylon-6T UL94V-0
P/N:CNT-M200-1*XX-GM-A/B/W/E




28、2.0mm双排排针，SMT
Spec:2.0mm Pin Header,Dual Row, SMT
Positions:4-80PIN
Plastics Height:1.0 / 1.5/2.0mm
Materials:Nylon-6T UL94V-0
P/N:CNT-M200-2*XX-GM-A/B/W



29、2.0mm双排双层排针，SMT,带柱
Spec:2.0mm Pin Header,Dual Row,Board Spacer,SMT,With Peg
Positions:4-80PIN
Plastics Height:1.0 / 1.5/2.0mm
Materials:Nylon-6T UL94V-0
P/N:CNT-M200-2*XX-GM-A/B/W/E-P



30、2.0mm三排排针，180度直插
Spec:2.0mm Pin Header,Triple Row,Straight Dip
Positions:3-120PIN
Plastics Height:2.0mm
Materials:Nylon-6T UL94V-0
P/N:CNT-M200-3*XX-GS-A/B



31、2.0mm三排排针，90度直插
Spec:2.0mm Pin Header,Triple Row,Right Angle Dip
Positions:3-120PIN
Plastics Height:2.0mm
Materials:Nylon-6T UL94V-0
P/N:CNT-M200-3*XX-GD-A/B/E



32、2.0mm单排排针，90度SMT
Spec:2.0mm Pin Header,Single Row,Right angle SMT
Positions:2-40PIN
Plastics Height:2.0mm
Materials:LCP
P/N:CNT-M200-1*XX-GDM-A/B/E


CNT 肯耐特电子 CONNECTOR CONNECTOR ELECTRONICS ——专业连接器制造商



33、2.0mm双排排针，90度SMT
Spec:2.0mm Pin Header,Dual Row,Right angle SMT
Positions:4-80PIN
Plastics Height:2.0mm
Materials:LCP
P/N:CNT-M200-2*XX-GDM-A/B/E




34、2.0mm双排排针，90度
Spec:2.0mm Pin Header,Dual Row,Right angle
Positions:4-80PIN
Plastics Height:4.3mm
Materials:Nylon-6T UL94V-0
P/N:CNT-M200-2*XX-GD-430



35、2.0mm简易牛角，180度直插
Spec:2.0mm Box Header,Straight
Positions:10-50PIN
Plastics Height:5.6mm
Materials: Nylon-6T UL94V-0
P/N:CNT-B200-2*XX-GS-H/B




36、2.0mm简易牛角，90度直插
Spec:2.0mm Box Header,Right angle
Positions:10-50PIN
Plastics Height:5.6mm
Materials: Nylon-6T UL94V-0
P/N:CNT-B200-2*XX-GD-B/E




37、2.0mm简易牛角，SMT
Spec:2.0mm Box Header,SMT
Positions:10-50PIN
Plastics Height:5.6mm
Materials: Nylon-6T UL94V-0
P/N:CNT-B200-2*XX-GM-H/W




38、2.0mm勾勾牛角，180度
Spec:2.0mm Box Header with Lock Straight
Positions:6-64PIN
Plastics Height:12.9mm
Materials: Nylon-6T UL94V-0
P/N:CNT-G200-2*XX-GS




39、2.0mm双排母座，180度直插
Spec:2.0mm Female Header,Dual Row,Straight DIP
Positions:4-80PIN
Plastics Height:4.0/4.3/4.6mm
Materials: Nylon-6T UL94V-0
P/N:CNT-F200-2*XX-GS-H/B




40、2.0mm单排母座，SMT
Spec:2.0mm Female Header,Single Row,Smt
Positions:2-40PIN
Plastics Height:4.0/4.3/4.6mm
Materials: Nylon-6T UL94V-0
P/N:CNT-F200-1*XX-GM-H/W




41、2.0mm双排母座，SMT
Spec:2.0mm Female Header,Dual Row,Smt
Positions:2-40PIN
Plastics Height:4.0/4.3/4.6mm
Materials: Nylon-6T UL94V-0
P/N:CNT-F200-2*XX-GM-H/W




42、2.0mm单排母座，90度
Spec:2.0mm Female Header,Single Row,Right angle
Positions:2-40PIN
Plastics Height:4.3mm
Materials: Nylon-6T UL94V-0
P/N:CNT-F200-1*XX-GD-H/B




43、2.0mm单排母座，180度
Spec:2.0mm Female Header,Single Row,Straight
Positions:2-40PIN
Plastics Height:6.35mm
Materials: Nylon-6T UL94V-0
P/N:CNT-F200-1*XX-GS-635/2.4




44、2.0mm双排母座，180度
Spec:2.0mm Female Header,Single Row,Straight
Positions:2-40PIN
Plastics Height:6.35mm
Materials: LCP UL94V-0
P/N:CNT-F200-2*XX-GS-635/2.4




45、2.0mm双排母座，180度侧插
Spec:2.0mm Female Header,Dual Row,Side angle Dip
Positions:4-80PIN
Plastics Height:5.0mm
Materials: Nylon-6T UL94V-0
P/N:CNT-F200-2*XX-GSC-500




46、2.0mm双排母座，180度蜈蚣脚插
Spec:2.0mm Female Header,Dual Row, Dip
Positions:4-80PIN
Plastics Height:5.0mm
Materials: Nylon-6T UL94V-0
P/N:CNT-F200-2*XX-GC-430




47、2.54mm双排排针，DIP180度
Spec:2.54mm Pin Header,Dual Row, Straight
Positions:4-80PIN
Plastics Height:1.5/2.0/2.5mm
Materials:PBT UL94V-0
P/N:CNT-M254-2*XX-GS-A/B




48、2.54mm双排双层排针，DIP180度
Spec:2.54mm Pin Header,Dual Row, Board Spacer,Straight
Positions:4-80PIN
Plastics Height:1.5/2.0/2.5mm
Materials:PBT UL94V-0
P/N:CNT-M254-2*XX-GS-A/E/B



49、2.54mm双排排针，90度
Spec:2.54mm Pin Header,Dual Row,Right angle
Positions:4-80PIN
Plastics Height: 7.4mm
Materials:PBT UL94V-0
P/N:CNT-M254-2*XX-GD-740




50、2.54mm双排排针，90度
Spec:2.54mm Pin Header,Dual Row,Right Angle
Positions:4-80PIN
Plastics Height:1.5/2.0/2.5mm
Materials:PBT UL94V-0
P/N:CNT-M254-2*XX-GD-A/B/E




51、2.54mm三排排针，DIP180度
Spec:2.54mm Pin Header,Triple Row, Straight
Positions:6-120PIN
Plastics Height: 2.5mm
Materials:PBT UL94V-0
P/N:CNT-M254-3*XX-GS-A/B



52、2.54mm双排排针，SMT
Spec:2.54mm Pin Header,Dual Row, SMT
Positions:4-80PIN
Plastics Height:1.5/2.0/2.5mm
Materials:Nylon 6T UL94V-0
P/N:CNT-M254-2*XX-GM-A/B/W




53、2.54mm双排双层排针，SMT，带柱
Spec:2.54mm Pin Header,Dual Row,Board Spacer, SMT, Peg
Positions:4-80PIN
Plastics Height:1.5/2.0/2.5mm
Materials:Nylon 6T UL94V-0
P/N:CNT-M254-2*XX-GM-A/B/W/E-P



54、2.54mm单排排针，90度SMT
Spec:2.54mm Pin Header,Single Row,Right angle SMT
Positions:2-40PIN
Plastics Height: 2.5mm
Materials:Nylon 6T UL94V-0
P/N:CNT-M254-1*XX-GDM-A/B/E




55、2.54mm双排排针，90度SMT
Spec:2.54mm Pin Header,Dual Row,Right angle SMT
Positions:4-80PIN
Plastics Height: 2.5mm
Materials:Nylon 6T UL94V-0
P/N:CNT-M254-2*XX-GDM-A/B/E




56、2.54mm双排双层排针，90度
Spec:2.54mm Pin Header,Dual Row, Board Spacer,Right Angle
Positions:4-80PIN
Plastics Height:1.5/2.0/2.5mm
Materials:PBT UL94V-0
P/N:CNT-M254-2*XX-GD-A/E/B/E




57、2.54mm简易牛角，180度
Spec:2.54mm Box Header,Straight
Positions:6-64PIN
Plastics Height: 9.1mm
Materials:PBT UL94V-0
P/N:CNT-B254-2*XX-GS-H/B



58、2.54mm加高简易牛角，180度
Spec:2.54mm Box Header,Board Spacer,Straight
Positions:6-64PIN
Plastics Height: H
Materials:PBT UL94V-0
P/N:CNT-B254-2*XX-GS-H/B



59、2.54mm简易牛角，90度
Spec:2.54mm Box Header,Right angle
Positions:6-64PIN
Plastics Height: 9.1mm
Materials:PBT UL94V-0
P/N:CNT-B254-2*XX-GD-H/B




60、2.54mm简易牛角，SMT
Spec:2.54mm Box Header,SMT
Positions:6-64PIN
Plastics Height: 9.1mm
Materials:NYLON 6T UL94V-0
P/N:CNT-B254-2*XX-GM-H/W




61、2.54mm勾勾牛角，180度
Spec:2.54mm Box Header With Lock,Straight
Positions:6-64PIN
Plastics Height: 9.1mm
Materials:PBT UL94V-0
P/N:CNT-G254-2*XX-GS-3.2




62、2.54mm勾勾牛角，90度
Spec:2.54mm Box Header With Lock,Right angle
Positions:6-64PIN
Plastics Height: 9.1mm
Materials:PBT UL94V-0
P/N:CNT-G254-2*XX-GD-3.2




63、2.54mm单排母座，180度，U型端子
Spec:2.54mm Female Header ,Single Row,Straight ,U Type
Positions:2-40PIN
Plastics Height: 5.0/8.5/7.1mm
Materials:PBT UL94V-0
P/N:CNT-F254-1*XX-GS-H/B-U




64、2.54mm双排母座，180度，U型端子
Spec:2.54mm Female Header ,Dual Row,Straight ,U Type
Positions:4-80PIN
Plastics Height: 5.0/8.5/7.1mm
Materials:PBT UL94V-0
P/N:CNT-F254-2*XX-GS-H/B-U




65、2.54mm单排母座，90度，U型端子
Spec:2.54mm Female Header ,Single Row,Right Angle,U Type
Positions:2-40PIN
Plastics Height: 5.0/8.5/7.1mm
Materials:PBT UL94V-0
P/N:CNT-F254-1*XX-GD-H/B-U




66、2.54mm双排母座，90度，U型端子
Spec:2.54mm Female Header ,Dual Row,Right Angle,U Type
Positions:2-40PIN
Plastics Height: 5.0/8.5/7.1mm
Materials:PBT UL94V-0
P/N:CNT-F254-2*XX-GD-H/B-U




67、2.54mm单排母座，180度，Y型端子
Spec:2.54mm Female Header ,Single Row,Straight,Y Type
Positions:2-40PIN
Plastics Height: 5.7/8.5mm
Materials:PBT UL94V-0
P/N:CNT-F254-1*XX-GS-850/B



68、2.54mm双排母座，180度，Y型端子
Spec:2.54mm Female Header ,Dual Row,Straight,Y Type
Positions:4-80PIN
Plastics Height:5.7/ 8.5mm
Materials:PBT UL94V-0
P/N:CNT-F254-2*XX-GS-850/B




69、2.54mm双排加高母座，180度，Y型端子
Spec:2.54mm Female Header ,Dual Row,Board Spacer,Straight,Y Type
Positions:4-80PIN
Plastics Height: 16.12mm
Materials:PBT UL94V-0
P/N:CNT-F254-2*XX-GS-1612/3.0



70、2.54mm双排母座，180度，Y型端子,带凸点
Spec:2.54mm Female Header ,Dual Row, Y Type
Positions:4-80PIN
Plastics Height: 8.5mm
Materials:PBT UL94V-0
P/N:CNT-F254-2*XX-GS-850/B-T




71、2.54mm双排加高母座，180度，Y型端子
Spec:2.54mm Female Header ,Dual Row, Board Spacer,Y Type
Positions:4-80PIN
Plastics Height: 11.0mm
Materials:PBT UL94V-0
P/N:CNT-F254-2*XX-GS-1100/B



72、2.54mm三排母座，180度，Y型端子
Spec:2.54mm Female Header ,Triple Row,,Y Type
Positions:6-120PIN
Plastics Height: 8.5mm
Materials:PBT UL94V-0
P/N:CNT-F254-3*XX-GS-850/B




73、2.54mm单排母座，SMT，U型端子
Spec:2.54mm Female Header ,Single Row, SMT
Positions:2-40PIN
Plastics Height: 7.1mm
Materials:Nylon 6T
P/N:CNT-F254-1*XX-GM-710




74、2.54mm双排母座，SMT，U型端子
Spec:2.54mm Female Header ,Dual Row, SMT
Positions:4-80PIN
Plastics Height: 7.1mm
Materials:Nylon 6T
P/N:CNT-F254-2*XX-GM-710




75、2.54mm单排母座，90度，Y型端子
Spec:2.54mm Female Header ,Single Row,Right angle Y Type
Positions:4-80PIN
Plastics Height:5.7/ 8.5mm
Materials:PBT UL94V-0
P/N:CNT-F254-1*XX-GD-H/B




76、2.54mm双排母座，90度，Y型端子
Spec:2.54mm Female Header ,Dual Row,Right angle Y Type
Positions:4-80PIN
Plastics Height:5.7/ 8.5mm
Materials:PBT UL94V-0
P/N:CNT-F254-2*XX-GD-H/B




77、2.54mm单排母座，180度，蜈蚣脚
Spec:2.54mm Female Header ,Single Row,Straight
Positions:2-40PIN
Plastics Height:5.0mm
Materials:PBT UL94V-0
P/N:CNT-F254-1*XX-GC-500




78、2.54mm双排母座，180度，蜈蚣脚
Spec:2.54mm Female Header ,Dual Row,Straight
Positions:4-80PIN
Plastics Height:5.0mm
Materials:PBT UL94V-0
P/N:CNT-F254-2*XX-GC-500



79、2.54mm单排侧插母座，180度
Spec:2.54mm Female Header ,Single Row,Side entry Straight
Positions:2-40PIN
Plastics Height:3.4mm
Materials:Nylon 6T
P/N:CNT-F254-1*XX-GSC-340




80、2.54mm单排母座，侧插SMT
Spec:2.54mm Female Header ,Single Row,Side entry SMT
Positions:2-40PIN
Plastics Height:3.4mm
Materials:Nylon 6T
P/N:CNT-F254-1*XX-GMC-340/11.0




81、2.54mm双排母座，侧插母座180度
Spec:2.54mm Female Header ,Single Row,Side entry Straight
Positions:4-80PIN
Plastics Height:5.95mm
Materials:Nylon 6T
P/N:CNT-F254-2*XX-GSC-595




82、2.54mm双排母座，侧插SMT
Spec:2.54mm Female Header ,Dual Row,Side entry SMT
Positions:2-40PIN
Plastics Height:5.95mm
Materials:Nylon 6T
P/N:CNT-F254-2*XX-GMC-595/11.0



83、3.96mm单排排针，180度
Spec:3.96mm Pin Header ,Single Row, Straight
Positions:2-24PIN
Plastics Height:3.18mm
Materials:LCP
P/N:CNT-M396-1*XX-TS-A/B



84、3.96mm单排排针，90度
Spec:3.96mm Pin Header ,Single Row, Straight
Positions:2-24PIN
Plastics Height:3.18mm
Materials:LCP
P/N:CNT-M396-1*XX-TD-A/B/E



85、3.96mm单排母座，180度
Spec:3.96mm Female Header ,Single Row, Straight
Positions:2-24PIN
Plastics Height:8.89mm
Materials:LCP
P/N:CNT-F396-1*XX-TS-889



86、短路帽
Spec:2.0/2.54 MINI JUMPER
Positions:2-8PIN
Plastics Height:6.0mm
Materials:PBT
P/N:CNT-MJ254-02/2*XX-GS-600



87、压接式FC
Spec:2.0/2.54 FC
Positions:6-64PIN
Plastics Height:
Materials:PBT
P/N:CNT-FC254/200-XX



88、压接式FD
Spec:2.0/2.54 FD，DIP
Positions:6-64PIN
Plastics Height:
Materials:PBT
P/N:CNT-FD254/200-XX




89、4.2mm插座，双排180度
Spec:4.2MM Socket Double row Straight
Positions:2-24PIN
Materials:Nylon
P/N:CNT-W420-2*XX-TS



90、3.96mm插座，单排180度
Spec:3.96 MM Socket Single row Straight
Positions:2-12PIN
Materials:Nylon
P/N:CNT-W396-1*XX-TS-1280




91、3.96mm插座，单排90度
Spec:3.96 MM Socket Single row Right angle
Positions:2-12PIN
Materials:Nylon
P/N:CNT-W396-1*XX-TD-1280




92、3.96mm插座，单排180度
Spec:3.96 MM Socket Single row Straight
Positions:2-13PIN
Materials:Nylon
P/N:CNT-W396-1*XX-TS-940




93、3.96mm插座，单排90度
Spec:3.96 MM Socket Single row Right angle
Positions:2-13PIN
Materials:Nylon
P/N:CNT-W396-1*XX-TD-940




94、2.5mm插座，单排180度
Spec:2.5MM Socket Single row ,Straight
Positions:2-15PIN
Materials:Nylon
P/N:CNT-W250-1*XX-TS




95、2.5mm插座，单排90度
Spec:2.5MM Socket Single row ,Right angle
Positions:2-15PIN
Materials:Nylon
P/N:CNT-W250-1*XX-TD




96、2.0mm插座，单排180度
Spec:2.0 MM Socket Single row ,Straight
Positions:2-15PIN
Materials:Nylon
P/N:CNT-W200-1*XX-TS




97、2.0mm插座，单排90度
Spec:2.0 MM Socket Single row ,Right angle
Positions:2-15PIN
Materials:Nylon
P/N:CNT-W200-1*XX-TD




98、2.54mm插座，单排180度
Spec:2.54MM Socket Single row ,Straight
Positions:2-20PIN
Materials:Nylon
P/N:CNT-W254-1*XX-TS-1140




99、2.54mm插座，单排90度
Spec:2.54MM Socket Single row ,Straight
Positions:2-20PIN
Materials:Nylon
P/N:CNT-W254-1*XX-TD-1140




100、2.0mm插座，立式SMT
Spec:2.0 MM Socket Straight SMT
Positions:2-16PIN
Materials:Nylon
P/N:CNT-W200-1*XX-TSM




101、2.0mm插座，卧式SMT
Spec:2.0 MM Socket Right angle SMT
Positions:2-16PIN
Materials:Nylon
P/N:CNT-W200-1*XX-TDM



102、2.0mm插座，双排180度
Spec:2.0 MM Socket Straight DIP
Positions:4-40PIN
Materials:Nylon
P/N:CNT-W200-2*XX-TS




103、2.5mm插座，单排180度，圆针
Spec:2.5 MM Socket Straight DIP
Positions:2-16PIN
Materials:Nylon
P/N:CNT-W250-1*XX-TS-590




104、2.5mm插座，单排90度，圆针
Spec:2.5 MM Socket Right angle DIP
Positions:2-16PIN
Materials:Nylon
P/N:CNT-W250-1*XX-TD-590




105、1.5mm插座，单排180度
Spec:1.5 MM Socket Straight DIP
Positions:2-16PIN
Materials:Nylon
P/N:CNT-W150-1*XX-TS



106、1.5mm插座，单排90度
Spec:1.5 MM Socket Right angle DIP
Positions:2-16PIN
Materials:Nylon
P/N:CNT-W150-1*XX-TD




107、1.25mm插座，单排180度
Spec:1.25 MM Socket Straight DIP
Positions:2-16PIN
Materials:Nylon
P/N:CNT-W125-1*XX-TS



108、1.25mm插座，单排180度SMT
Spec:1.25 MM Socket Straight SMT
Positions:2-16PIN
Materials:Nylon
P/N:CNT-W125-1*XX-TSM




109、1.25mm插座，单排90度SMT
Spec:1.25 MM Socket Right angle SMT
Positions:2-16PIN
Materials:Nylon
P/N:CNT-W125-1*XX-TDM




110、1.0mm插座，单排180度SMT
Spec:1.0 MM Socket Straight SMT
Positions:2-16PIN
Materials:Nylon
P/N:CNT-W100-1*XX-TSM



111、1.0mm插座，单排90度SMT
Spec:1.0 MM Socket Right angle SMT
Positions:2-16PIN
Materials:Nylon
P/N:CNT-W100-1*XX-TDM




112、圆孔IC脚座，单排180度
Spec:IC Socket,Single Row,DIP
Pitch:1.27/2.0/2.54mm
Height:3.0mm




113、圆孔IC脚座，单排180度
Spec:IC Socket,Single Row,DIP
Pitch:2.54mm
Height:7.0mm




114、圆孔IC脚座，双排180度
Spec:IC Socket,Double Row,DIP
Pitch:1.27/2.0/2.54mm
Height:3.0mm




115、圆孔IC脚座，单排90度
Spec:IC Socket,Single Row,Right angle DIP
Pitch:2.54mm
Height:7.0mm




116、圆PIN公座，单排90度
Spec:Round pin header,Single row,Right angle
Pitch: 1.27/2.0/2.54mm
Height:2.8mm




117、IC脚座，窄体，180度DIP
Spec:IC Socket,Staight DIP
Pitch: 2.54mm
W:7.62mm



118、IC脚座，宽体，180度DIP
Spec:IC Socket,Staight DIP
Pitch: 2.54mm
W:15.24mm




119、PLCC插座SMT
Spec:PLCC Socket,SMT
Pitch: 2.54mm
No of
Pins:20/28/32/44/52/68/84PIN



120、2.54间距双面接FPC插座直插180度
Spec:2.54Pitch FPC Straight DIP
No of pins:4-40pin



121、1.25间距FPC插座直插180度
Spec:1.25Pitch FPC Straight DIP
No of pins:4-35pin



122、1.25间距FPC插座直插90度
Spec:1.25Pitch FPC Right angle DIP
No of pins:4-35pin




123、1.0间距卧贴下接式掀盖式FPC插座
Spec:1.0 Pitch FPC Right angle SMT
No of pins:3-35pin



124、1.0间距卧贴下接式抽屉式FPC插座
Spec:1.0 Pitch FPC Right angle SMT
No of pins:3-35pin




125、1.0间距卧贴双面接FPC插座
Spec:1.0 Pitch FPC Right angle SMT
No of pins:4-40pin



126、1.0间距单面接FPC插座直插180度
Spec:1.0 Pitch FPC Straight DIP
No of pins:3-35pin




127、1.0间距双面接FPC插座直插180度
Spec:1.0 Pitch FPC Straight DIP
No of pins:3-40pin



128、1.0间距双面接FPC插座直插90度
Spec:1.0 Pitch FPC Right angle DIP
No of pins:3-40pin

CNT 肯耐特电子 CONNECTOR CONNECTOR ELECTRONICS ——专业连接器制造商



129、1.0间距立贴单面接FPC插座
Spec:1.0 Pitch FPC Straight SMT Socket
No of pins:2-29pin



130、1.0间距立贴掀盖式一字脚FPC插座
Spec:1.0 Pitch FPC Straight SMT Socket
No of pins:4-40pin



131、0.5间距卧贴上接式抽屉式FPC插座
Spec:0.5Pitch FPC Right angle SMT
No of pins:4-40pin



132、0.5间距立贴抽屉式一字脚FPC插座
Spec:0.5Pitch FPC Straight SMT Socket
No of pins:4-40pin



133、0.5间距立贴FPC插座
Spec:0.5Pitch FPC Straight SMT Socket
No of pins:4-60pin



134、0.5间距卧贴上接式掀盖FPC插座
Spec:0.5Pitch FPC Right angle SMT
No of pins:4-80pin



135、6.3插片
Spec:6.3 Teminal
DIP Tin Plated



136、3.0间距双排插座180度直插
Spec:PH3.0 Socket,Dual Row,Straight DIP



137、3.0间距双排插座90度直插
Spec:PH3.0 Socket,Dual Row,Right angle



138、MINI DIN JACK
Spec:Mini Din Jack,8Pin DIP




139、Sim卡座
Spec:Sim Socket card,6PIN smt



140、PC卡座
Spec:PC card Plug



141、RJ插座
单口,包壳香菇脚8P8C90度



142、RJ插座
6P有耳无壳插座90度



143、RJ插座
8P包壳90度含灯左黄右绿插座



144、RJ插座
4脆包壳10P8C插座



145、RJ插座
2*4插座8P8C包壳无弹圆氏插座



146、USB插座
USB-A母焊线式



147、USB插座
USB-B母，焊板90度DIP



148、USB插座
MICRO 5P-B公超薄焊线一体



149、USB插座
MINI-B母5P/90度DIP




150、USB插座
MINI-B母5P/SMT




151、USB插座
USB-A公90度DIP



152、USB插座
USB-A母90度DIP



153、USB插座
USB-A母90度DIP侧插



154、USB插座
USB-A母180度DIP



155、USB插座
USB-A母单层90度
DIP沉板式



156、USB插座
USB-A母双层有弹




157、USB插座
USB-B母90度DIP



158、D-SUB
D-SUB母座,15p,90度



159、D-SUB
D-SUB公座,25P,90度



160、D-SUB
D-SUB母座,9p,90度



161、D-SUB
D-SUB公座,9P,90度



162、D-SUB
D-SUB公座,9P,180度，
后铆鱼叉



163、D-SUB
D-SUB母座,9P,180度，
后铆鱼叉




164、D-SUB
D-SUB公座,25P,180度，焊线式



165、D-SUB
D-SUB母座,15P,180度
焊线式



166、D-SUB
D-SUB双层9PIN公/母90度



167、D-SUB
D-SUB双层9PIN母/15PIN母,90度



168、D-SUB
D-SUB金属外壳



169、D-SUB
D-SUB护套
















CONNECTOR ELECTRONICS

CNT 肯耐特电子 CONNECTOR

CONNECTOR ELECTRONICS

——专业连接器制造商



科学提升质量

服务凝集力量

CNT 肯耐特电子 CONNECTOR | 专业更专注！





















美国UL认证



